LaView USA
Innovation That Secures

Security for Your Business and Home

LV-KDV1402B6BP

The Power of 960H

Digital Surveillance System

Take advantage of 960H high resolution recording that brings true wide screen images to your wide screen TV or monitor. Experience greater detail, and sharper images to improve the security of your business or home (Hard Drive Optional)

1. Video in
2. Video out
3. USB interface
4. HDMI interface
5. VGA interface
6. Audio in, RCA connector
7. Audio out, RCA connector
8. LAN network interface
9. RS-485 serial
10. 12VDC power input
11. Power switch
12. GND

600 TVL IR Bullet Camera

LV-CBA3263BP	
Camera	
Image Sensor	1/3″ sensor
Signal System	NTSC/PAL
Effective Pixels	720 (H) × 480 (V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	PAL: 1/25 s to 1/15,000 s NTSC: 1/30 s to 1/15,000 s
Lens	3.6 mm Angle of view: 68.4°
Infrared LEDs	12 pc
IR Range	65ft(20m)
Angle Adjustment	Pan: 0 - 360° , Tilt: 0 - 90° , Rotation: 0 - 360°
Day & Night	IR cut filter with auto switch
Horizontal Resolution	600 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75Ω/BNC)
S/N Ratio	More than 52 dB
General	
Working Temperature/Humidity	-40 ° C - 60 ° C (-40 ° F - 140 ° F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC
Power Consumption	Max. 2 W (Max. 5 W with IR cut filter on)
Ingress Protection	IP66
Lens Mount	M12
Dimensions	Φ70×149.5 mm (Φ2.76″ ×5.89″)
Weight	300 g (0.66 lbs)

960H 4 Channel DVR

LV-D2104CS	
Video/Audio input	
Video compression	H.264
Video input	4-ch
Video input interface	BNC (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
Audio compression	G.711u
Audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Video/Audio output	
HDMI / VGA output	1-ch, resolution: 1080P: 1920×1080/60Hz; SXGA: 1280×1024/60Hz; 720P: 1280×720/60Hz; XGA: 1024×768/60Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: NTSC: 704 × 480, PAL: 704 × 576
Encoding resolution	WD1 / 4CIF / 2CIF / CIF / QCIF
Frame rate	WD1 / 4CIF / 2CIF @15 fps(N); CIF / QCIF @ /30 fps (N)
Video bit rate	32Kbps~3072Kbps,or use defined(Max.3072Kbps)
Audio output	1-ch, RCA (Linear, 1 kΩ)
Audio bit rate	64 Kbps
Dual-stream	Support; Sub-stream @ CIF / QCIF
Stream type	Video, Video & Audio
Synchronous playback	4-ch
Hard disk	
SATA	1 SATA interface
Capacity	Up to 4TB capacity
External interface	
Network interface	1, RJ45 10M / 100M Ethernet interface
Serial interface	1 RS-485 interface, half-duplex
USB interface	2, USB2.0
General	
Power supply	12 VDC
Consumption	⩽ 10 W
Working temperature	-10 ° C ~ +55 ° C
Working humidity	10% ~ 90%
Chassis	Standalone 1U chassis
Dimensions	315 × 230 × 45 mm
Weight	⩽ 2 kg (without hard disk or DVD-R/W)